

# Power cable

Aluminum, halogen-free, flame retardant



### Construction:

- 1. Conductor: Solid, annealed aluminum wire class 1 IEC 60228.
- 2. Insulation: Flame retardant polyolefin. Color identification: grey and black.
- 3. Shield: AL/PET tape with annealed aluminum wires. Max resistance 4.95 Ω/km.
- 4. Sheath: Flame retardant, black polyolefin. Sunlight resistant. Example of marking: "NKT TJL492324/CU 2x10 AWG (2x8 mm<sup>2</sup>) Max 600 V 90C DRY CT Use Sun Res"

### Application:

Halogen free, flame retardant and shielded aluminum cable for power supply to radio and other telecom equipment. Sunlight resistant. Indoor and outdoor use. *Note. Make sure connection terminals are compatible with aluminum conductors.*

### Properties:

Rated voltage	Max 600 V	Fire classification	IEC 60332-3-24 (Cat C)
Minimum operating temperature	-20°C (-40°C when fixed)	Fulfils low voltage directive, CE	Yes
Maximum operating temperature	+90°C	Fulfils RoHS	Yes
Minimum bending radius	8 x Outer diameter (4 x OD when fixed)	Fulfils REACH	Yes

---

**Technical data:**

No. of cores and cross-section mm <sup>2</sup>	Outer diameter mm	Cable weight kg/km	Effective resistance of conductor Ω/km	Inductance μH/m	Part number
2 x 10 Al	9.7	113	3.39	0.6	TJL492324
2 x 6 Cu*	9.3	167	3.39	0.6	TFL492324
2 x 16 Al	11.2	157	1.95	0.6	TJL492325
2 x 10 Cu*	10.9	248	1.95	0.6	TFL492325
2 x 25 Al	13.3	230	1.24	0.6	TJL492326
2 x 16 Cu*	13.0	349	1.24	0.6	TFL492326

\*Equivalent performance cable with copper conductors for comparison

All rights reserved. Any unauthorized usage, redistribution or reproduction of part or all of the content in any form will constitute an infringement of copyright. The data are only indicative and should not be considered a binding representation or warranty from NKT concerning a product's properties or usability. The data page is not exhaustive and should be read in conjunction with NKT other product data sheets, whether published or not. NKT reserves the right to change the data page without prior notice.

Influence on the environment. The product does not have any negative influence on the environment.